



- NOTES:
- 1. MATERIAL: Dia=1.5 mm SUS316 Stainless Steel Wire.
 - 2. FINISH: Natrual
 - 3. FINISH MUST WITHSTAND 200HR (FOR OUTDOOR APPLICATION) OR 1000HR (FOR COASTAL ENVIRONMENT APPLICATION) OF ASTM B117 SALT SPRAY TEST
 - 4. MATERIAL MUST COMPLY WITH RoHS AND REACH REQ.
 - 5. NOT ALLOW BURRS, FLASH, DIRT, SINK MARK, SCRAP MARK, ABRASIVE AND ANY IMPERFECTION ON THE PARTS SURFACE
 - 6. ALL UNSPECIFIED RADII ARE 0.5mm
 - 7. DETAILS DIMENSION REFER TO 3D FILE
 - 8. CONTROL DIMENSIONS

NEXT ASSY	USED ON
APPLICATION	

ITEM NO.	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	MATERIAL SPECIFICATION	QTY REQD
PARTS LIST				
THIS DOCUMENT CONTAIN INFORMATION PROPRIETARY TO TRAXON TECHNOLOGIES LTD. USE OR DISCLOSURE WITHOUT WRITTEN PERMISSION BY TRAXON IS EXPRESSLY FORBIDDEN. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MM. AND TOLERANCES ARE: FRACTIONS DECIMALS ANGLES Refer to ISO 2768-m MATERIAL FINISH		APPROVALS DRAWN CHECKED RESP ENG MFG ENG QUAL ENG	DATE	MODEL
		See Notes		Our Brand traxon OSRAM
		See Notes		AL Dot Series
		See Notes		Stainless Steel Mesh Grid_MG-100
SIZE A3		DWG. NO. -	REV. A	
SCALE 1:10 CAD FILE:				SHEET 4 OF 4

CONFIDENTIAL