



- NOTES:
- MATERIAL: Dia.=1.5 mm SUS316 Stainless Steel Wire.
 - FINISH: Natrual.
 - FINISH MUST WITHSTAND 200HR (FOR OUTDOOR APPLICATION) OR 1000HR (FOR COASTAL ENVIRONMENT APPLICATION) OF ASTM B117 SALT SPRAY TEST
 - MATERIAL MUST COMPLY WITH RoHS AND REACH REQ.
 - NOT ALLOW BURRS, FLASH, DIRT, SINK MARK, SCRAP MARK, ABRASIVE AND ANY IMPERFECTION ON THE PARTS SURFACE
 - DETAILS DIMENSION REFER TO 3D FILE
 - CONTROL DIMENSIONS

Remark :

- The MG frame is by others.
- The "X" & "Y" dimensions of grid is based on the tensioning.

AL Dot XS MG Bracket

ITEM NO.	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	MATERIAL SPECIFICATION	QTY REQD
PARTS LIST				
THIS DOCUMENT CONTAIN INFORMATION PROPRIETARY TO TRAXON TECHNOLOGIES LTD. USE OR DISCLOSURE WITHOUT WRITTEN PERMISSION BY TRAXON IS EXPRESSLY FORBIDDEN.			Our Brand	
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MM. AND TOLERANCES ARE: FRACTIONS DECIMALS ANGLES			traxon	
Refer to ISO 2768-m			OSRAM	
See Notes			AL Dot XS	
See Notes			PART DESCRIPTION:	
See Notes			Stainless Steel Mesh Grid_MG -120	
See Notes			SIZE DWG. NO.	
See Notes			A2	
See Notes			SCALE 1:12 CAD FILE:	
See Notes			SHEET 1 OF 1	
See Notes			CONFIDENTIAL	