



- NOTES:
- MATERIAL: Dia.-1.5 mm SUS316 Stainless Steel Wire.
 - FINISH: Natrual.
 - FINISH MUST WITHSTAND 200HR (FOR OUTDOOR APPLICATION) OR 1000HR (FOR COASTAL ENVIRONMENT APPLICATION) OF ASTM B117 SALT SPRAY TEST
 - MATERIAL MUST COMPLY WITH RoHS AND Reach REQ.
 - NOT ALLOW BURRS, FLASH, DIRT, SINK MARK, SCRAP MARK, ABRASIVE AND ANY IMPERFECTION ON THE PARTS SURFACE
 - DETAILS DIMENSION REFER TO 3D FILE
 - CONTROL DIMENSIONS

- Remark :
- The MG frame is by others.
 - The "X" & "Y" dimensions of grid is based on the tensioning.

ITEM NO.	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	MATERIAL SPECIFICATION	QTY REQD
		PARTS LIST		
		THIS DOCUMENT CONTAIN INFORMATION PROPRIETARY TO TRAXON TECHNOLOGIES LTD. USE OR DISCLOSURE WITHOUT WRITTEN PERMISSION BY TRAXON IS EXPRESSLY FORBIDDEN.		
		UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MM. AND TOLERANCES ARE: FRACTIONS DECIMALS ANGLES		
		Refer to ISO 2768-m		
		MATERIAL	APPROVALS DRAWN	DATE
		See Notes	CHECKED	
		FINISH	RESP ENG	
		See Notes	MFG ENG	
		3RD ANGLE PROJECTION	QUAL ENG	
NEXT ASSY	USED ON			
APPLICATION				
				MODEL
				Our Brand
				traxon
				OSRAM
				AL Dot XS
				Part Description
				Stainless Steel Mesh Grid_MG-90
				SIZE DWG. NO.
				A2
				SCALE 1 : 10 CAD FILE
				REV. A
				SHEET 1 OF 1

CONFIDENTIAL