




NOTES:

- MATERIAL: Dia.=1.5 mm SUS316 Stainless Steel Wire.
- FINISH: Natrual.
- FINISH MUST WITHSTAND 200HR (FOR OUTDOOR APPLICATION) OR 1000HR (FOR COASTAL ENVIRONMENT APPLICATION) OF ASTM B117 SALT SPRAY TEST
- MATERIAL MUST COMPLY WITH RoHS AND REACH REQ.
- NOT ALLOW BURRS, FLASH, DIRT, SINK MARK, SCRAP MARK, ABRASIVE AND ANY IMPERFECTION ON THE PARTS SURFACE
- DETAILS DIMENSION REFER TO 3D FILE
- CONTROL DIMENSIONS

Remark :

- The MG frame is by others.
- The "X" & "Y" dimensions of the grid is based on the tensioning.

ITEM NO.		PART OR IDENTIFYING NO.		NOMENCLATURE OR DESCRIPTION		MATERIAL SPECIFICATION		QTY REQD	
				PARTS LIST					
<div><div>THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO TRAXON TECHNOLOGIES LTD. USE OR DISCLOSURE WITHOUT WRITTEN PERMISSION BY TRAXON IS EXPRESSLY FORBIDDEN.</div><div><div>Our Brand</div><div></div></div></div>						<div></div>			
<div>UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MM. AND TOLERANCES ARE: FRACTIONS DECIMALS ANGLES</div>				<div>APPROVALS DATE</div>		<div>MODEL</div>			
<div>Refer to ISO 2768-m</div>				<div>DRAWN</div>		<div>AL Dot XS</div>			
<div>MATERIAL</div>				<div>CHECKED</div>		<div>PART DESCRIPTION</div>			
<div>See Notes</div>				<div>RESP ENG</div>		<div>Stainless Steel Mesh Grid_MG-40</div>			
<div>FINISH</div>				<div>MFG ENG</div>		<div>SIZE DWG. NO.</div>		<div>REV. A</div>	
<div>See Notes</div>				<div>QUAL ENG</div>		<div>A2</div>		<div>SCALE 1 : 5 CAD FILE:</div>	
<div>NEXT ASSY USED ON</div>		<div>3RD ANGLE PROJECTION</div>				<div>SHEET 1 OF 1</div>			
<div>APPLICATION</div>		<div></div>							