



NOTES:

1. MATERIAL: Dia.=1.5 mm SUS316 Stainless Steel Wire.
2. FINISH: Natrual.
3. FINISH MUST WITHSTAND 200HR (FOR OUTDOOR APPLICATION) OR 1000HR (FOR COASTAL ENVIRONMENT APPLICATION) OF ASTM B117 SALT SPRAY TEST
4. MATERIAL MUST COMPLY WITH RoHS AND REACH REQ.
5. NOT ALLOW BURRS, FLASH, DIRT, SINK MARK, SCRAP MARK, ABRASIVE AND ANY IMPERFECTION ON THE PARTS SURFACE
6. DETAILS DIMENSION REFER TO 3D FILE
7. CONTROL DIMENSIONS

Remark :

- 1.) The MG frame is by others.
- 2.) The "X " & " Y " dimensions of the grid is based on the tensioning.

ITEM NO.		PART OR IDENTIFYING NO.		NOMENCLATURE OR DESCRIPTION		MATERIAL SPECIFICATION		QTY REQD	
PARTS LIST									
THIS DOCUMENT CONTAIN INFORMATION PROPRIETARY TO TRAXON TECHNOLOGIES LTD. USE OR DISCLOSURE WITHOUT WRITTEN PERMISSION BY TRAXON IS EXPRESSLY FORBIDDEN.						Our Brand		OSRAM	
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MM. AND TOLERANCES ARE: FRACTIONS DECIMALS ANGLES						APPROVALS		DATE	
Refer to ISO 2768-m						DRAWN		MODEL	
MATERIAL						CHECKED		AL Dot XS	
See Notes						RESP ENG		PART DESCRIPTION	
FINISH						MFG ENG		Stainless Steel Mesh_Grid_MG-80	
See Notes						QUAL ENG		SIZE DWG. NO.	
3RD ANGLE PROJECTION						A2		REV. A	
NEXT ASSY USED ON						SCALE 1 : 1		CAD FILE:	
APPLICATION						SHEET 1		OF 1	